

# TESAB



## TS3600 / TS3430

### TRACKED RINSERS

These high energy Screeners are used across a wide range of applications, including aggregate, coal, crusher circuits and wood chips. They are renowned for their fine sand screening and are impressing customers worldwide with their production capacities.

With class-leading TS-Range features like the aggressive High Energy Screenbox and user-friendly operation. Their unique size is designed to meet demands of operators who require significantly more screening capacity than a 10' or 11' screenbox.

### FEATURES & BENEFITS

- Fast set up time
- Low cost set-up – no crane hire required
- Easily converted to dry screen mode
- Ideal for hire fleets and contractors
- Wet and dry screening capabilities
- Dual power option
- Extra coupling facility to run additional equipment such as MWS Sand Screws and Stackers.
- Hydraulic catch box – Allows user to easily lift and lower the catch box
- 8 independently controlled spray bars on each deck delivering 2 bar/29 psi of water pressure at each nozzle

## RINSERS

42" (1050mm) feed conveyor enables high capacity screening.

TS3430 high energy 20' x 5' Top & middle deck 18' x 5' bottom deck.

TS3600 high energy 14x5 (4200x1524mm) screenbox provides comparable product capacity with other larger class competitor's models.

15ft (4267mm) grid opening allows the use of larger loading shovels.

Hydraulic Screenbox linkage system, allows great accessibility for screen change and enables optimum screen coverage at varying screenbox angles.

User friendly wedge system ensures faster screen changes.

## DIMENSION SPECIFICATION\*

### TS3600

Length	Width	Height
16.52m (54' - 2")	3.24m (10' - 8")	3.45m (11' - 4")

### TS3430

Length	Width	Height
18.2m (59' - 8")	3.24m (10' - 8")	3.45m (11' - 4")

\* Depending on material density and set-up